

DeLonghi ESAM 5600 Test Mode

Start test mode

1. Insert the mains plug
2. Push in the main switch on the back to turn ON (1)
3. Wait until the machine is in standby (display dark)
4. Open the service door
5. Press **P** , ☕ and ☕ at the same time and hold for more than 5 seconds
6. **SELECT TEST** appears on the display
7. Close the service door
8. Select the test using the corresponding key:

BUTTON	TEST	DISPLAY
CAFFELATTE	Test buttons	BUTTON
CAPPUCCINO	Test components	LOAD TEST MODE
LATTE MACCHIATO	System Reset	Language selection*
MILK	Self Test	blank

9. Leave test mode: Open the service door and wait approx. 15 seconds or the main switch to OFF (0)

Test buttons

The pressed key number is shown on the display according to the following image













* When your desired language appears, press the selection icon corresponding to OK on the display for a few seconds

DeLonghi ESAM 5600 Test Mode

Unit Test

The function of the following components can be checked by pressing the corresponding button. The respective component is activated as long as the button is held.

Button	Display	Function
P	HEATER ON	Switch on the heater
		?
	PUMP ON	Switch on the pump (only works with water in the tank!)
		?
	VAPORIZER ON	Switch on the steam generator
	EV1 ON	Switch on the rear solenoid valve
	EV2 ON	Switch on the front solenoid valve
	MOTOR UP LIMIT SWITCH UP	Move the brew group upwards
	EV1 ON EV2 ON	Upper limit switch reached
	GRINDER ON	Switch on both solenoid valves
	MOTOR DOWN LIMIT SWITCH DOWN	Move the brew group down Lower limit switch reached